


C32 ACERT

ENGINE



Specifications

	U.S. EPA Tier 4 Final	U.S. EPA Tier 4 Interim Equivalent
Engine Configuration ...	V-12, Diesel	V-12, Diesel
Bore x Stroke	145.0 x 162 mm (5.71 x 6.38 in) ..	145.0 x 162 mm (5.71 x 6.38 in)
Displacement	32.1 liters (1959 in ³)	32.1 liters (1959 in ³)
Ship Weight	3004 kg (6625 lbs)	3004 kg (6625 lbs)
Approximate Dimensions (engine only):		
Length	1874 mm (73.8 in)	1874 mm (73.8 in)
Width	1600 mm (63.0 in)	1600 mm (63.0 in)
Height	1370 mm (53.9 in)	1370 mm (53.9 in)

U.S. EPA Tier 4 Final Ratings

TA (ATAAC)	B Rating			C Rating (Intermittent)			D Rating		
	bkW	bhp	rpm	bkW	bhp	rpm	bkW	bhp	rpm
	746	1000	1800	839	1125	1800	895	1200	1800

U.S. EPA Tier 4 Interim Equivalent Ratings

TA (ATAAC)	C Rating (Intermittent)			D Rating		
	bkW	bhp	rpm	bkW	bhp	rpm
	839	1125	1800	895	1200	1800

U.S. EPA Tier 4 Final Nonroad emission standards. U.S. EPA Tier 4 Interim equivalent ratings available using U.S. EPA Flex provisions. Nonroad engines greater than 560 bkW (750 bhp) are not currently subject to EU emission standards.