


C11 ACERT

ENGINE



Specifications

China Stage III Nonroad, U.S. EPA Tier 3 Equivalent, EU Stage IIIA Equivalent

Engine Configuration . . .	In-Line 6, Diesel
Bore x Stroke	130 x 140 mm (5.12 x 5.51 in)
Displacement	11.1 liters (677 in ³)
Ship Weight	930 kg (2050 lbs)

Approximate Dimensions:

Length	1203 mm (47.4 in)
Width	1054 mm (41.5 in)
Height	1186 mm (46.7 in)

China Stage III Nonroad, U.S. EPA Tier 3 Equivalent, EU Stage IIIA Equivalent Ratings

A Rating (Continuous)			B Rating			C Rating (Intermittent)			D Rating			E Rating		
bkW	bhp	rpm	bkW	bhp	rpm	bkW	bhp	rpm	bkW	bhp	rpm	bkW	bhp	rpm
TA (ATAAC)														
242	325	1800-	261	350	1800-	287	385	1800-	313	420	1800-	336	450	1800-
		2100			2100			2100			2100			2100

Designed to meet China Stage III Nonroad emission standards. U.S. EPA Tier 3 Nonroad equivalent emission standards (not currently EPA certified). EU Stage IIIA Nonroad equivalent emission standards (non-current for EU). Available for other regulated and non-regulated areas.