


C1.5 ENGINE



Specifications

U.S. EPA Tier 4 Final, EU Stage IIIA

Engine Configuration . . .	In-Line 3, Diesel
Bore x Stroke	84 x 90 mm (3.3 x 3.5 in)
Displacement	1.496 liters (91 in ³)
Ship Weight	149 kg (328.5 lbs) (NA) 156.5 kg (345 lbs) (T)

Approximate Dimensions:

Length	572 mm (22.5 in) (NA, T)
Width	453 mm (17.8 in) (NA) 512 mm (20.2 in) (T)
Height	643 mm (25.3 in) (NA, T)

U.S. EPA Tier 4 Final Ratings

	C Rating (Intermittent)		
	bkW	bhp	rpm
NA			
	18.4	24.7	2100*
T			
	18.4	24.7	1800*
	25.2	33.8	2400
	27.0	36.2	2800
	27.6	37.0	3000

*Special application

EU Stage IIIA Ratings

	C Rating (Intermittent)		
	bkW	bhp	rpm
NA			
	20.9	28.0	2200
	22.3	29.9	2400
	23.4	31.4	2600
	24.4	32.7	2800
	25.1	33.7	3000
T			
	23.1	31.0	2200
	25.2	33.8	2400
	27.3	36.6	2600
	29.4	39.4	2800
	30.0	40.2	3000

U.S. EPA Tier 4 Final, EU Stage IIIA Nonroad emission standards.