


C0.5 | C0.7

ENGINES

C0.5



Specifications

	C0.5 U.S. EPA Tier 4 Interim Equivalent	C0.7 U.S. EPA Tier 4 Interim Equivalent
Engine Configuration . . .	In-Line 2, Diesel	In-Line 3, Diesel
Bore x Stroke	67 x 72 mm (2.6 x 2.8 in)	67 x 72 mm (2.6 x 2.8 in)
Displacement	0.5 liters (31 in ³)	0.76 liters (46.4 in ³)
Ship Weight (NA)	57 kg (126 lbs)	71 kg (156.5 lbs)
Approximate Dimensions:		
Length	407 mm (16.00 in)	480 mm (18.9 in)
Width	371 mm (14.60 in)	371 mm (14.6 in)
Height	523 mm (20.60 in)	528 mm (20.8 in)

C0.5 U.S. EPA Tier 4 Interim Equivalent Ratings

NA	C Rating (Intermittent)		
	bkW	bhp	rpm
	8.2	11.0	2800
	8.8	11.8	3000
	10.2	13.7	3600

C0.7 U.S. EPA Tier 4 Interim Equivalent Ratings

NA	C Rating (Intermittent)		
	bkW	bhp	rpm
	12.2	16.4	2800
	13.2	17.7	3000
	15.3	20.5	3600

U.S. EPA Tier 4 Interim Nonroad equivalent emission standards (not currently EPA certified). Available for other regulated and non-regulated areas.