



3612

# 3600 ENGINES

## Specifications

	3606	3608
<b>Engine Configuration</b> . . .	In-Line 6, Diesel . . . . .	In-Line 8, Diesel
<b>Bore x Stroke</b> . . . . .	280 x 300 mm (11 x 11.8 in) . . .	280 x 300 mm (11 x 11.8 in)
<b>Displacement</b> . . . . .	110.8 liters (6764 in <sup>3</sup> ) . . . . .	147.8 liters (9018 in <sup>3</sup> )
<b>Ship Weight</b> . . . . .	15 680 kg (34 500 lbs) . . . . .	19 000 kg (41 800 lbs)
<b>Approximate Dimensions:</b>		
<b>Length</b> . . . . .	3988 mm (157 in) . . . . .	4828 mm (190 in)
<b>Width</b> . . . . .	1748 mm (69 in) . . . . .	1748 mm (69 in)
<b>Height</b> . . . . .	2626 mm (103 in) . . . . .	2626 mm (103 in)

	3612	3616
<b>Engine Configuration</b> . . .	V-12, Diesel . . . . .	V-16, Diesel
<b>Bore x Stroke</b> . . . . .	280 x 300 mm (11 x 11.8 in) . . .	280 x 300 mm (11 x 11.8 in)
<b>Displacement</b> . . . . .	221.7 liters (13 527 in <sup>3</sup> ) . . . . .	295.6 liters (18 036 in <sup>3</sup> )
<b>Ship Weight</b> . . . . .	25 140 kg (55 300 lbs) . . . . .	29 950 kg (65 900 lbs)
<b>Approximate Dimensions:</b>		
<b>Length</b> . . . . .	4562 mm (180 in) . . . . .	5482 mm (216 in)
<b>Width</b> . . . . .	1704 mm (67 in) . . . . .	1704 mm (67 in)
<b>Height</b> . . . . .	3231 mm (127 in) . . . . .	3231 mm (127 in)

### 3606 Ratings

TA	Distillate A Rating (Continuous)		
	bkW	bhp	rpm
	1490	1998	750
	1560	2092	800
	1730	2319	900
	1850	2481	1000

### 3608 Ratings

TA	Distillate A Rating (Continuous)		
	bkW	bhp	rpm
	2080	2787	800
	2300	3080	900
	2460	3300	1000

### 3612 Ratings

TA	Distillate A Rating (Continuous)		
	bkW	bhp	rpm
	2980	3996	750
	3120	4184	800
	3460	4640	900
	3700	4962	1000

### 3616 Ratings

TA	Distillate A Rating (Continuous)		
	bkW	bhp	rpm
	4160	5579	800
	4600	6169	900
	4920	6598	1000

Non-certified. Available for global non-regulated areas.